

# DI 10 Dipslide Incubator



The Lovibond® DI 10 Incubator is designed for the reliable incubation of bacteriological slides, on-site, in a laboratory or even while mobile in a car or van.

National and European guidelines give practical advice on how to monitor, clean, test and ultimately control harmful legionella bacteria in water systems.

Dipslides provide a crucial part in the testing program, but must be used correctly and regularly as part of a planned regime, week on week to be of any meaningful value.

The incubation period and the incubation temperature should be the same each time the test is performed so that bacteria growth is controlled and consistent each time the test is performed. This allows for week by week comparisons to be made and high counts easier to identify. Dipslides are usually incubated at 30 C for 48 hours, but this can vary depending upon the specific application.

The Lovibond® DI 10 Incubator, when used in conjunction with dipslides, enables effective microbiological monitoring of cooling water in accordance with the many European guidelines.

### Highlights :

- Robust design
- Holds up to 12 dipslides
- Excellent temperature stability
- In-car operation

### Technical Data:

<b>Display</b>	1 x 16 bit Backlit LCD
<b>Power Supply</b>	12 V 110 V 240 V
<b>Dimensions Internal</b>	246 x 162 x 215 mm
<b>Dimensions without Work Top</b>	Dimensions without Work Top
<b>Dimensions</b>	Dimensions
<b>Weight</b>	1.7 kg

### Accessories:

Title	Part Number
Dipslide Holder	56B000801