

The SD series comprises a range of compact, easy-to-use, hand-held instruments for the accurate measurement of pH, ORP, Con, TDS or Salt. With robust housing and fully waterproof (IP67) casing, these testers are the ideal solution for in-situ testing in environmental, industrial or pool & spa applications.

The intuitive scroll-bar functionality and backlit display enable the easy measurement and simultaneous display of result, temperature, date/time and other measurement details. With 25 sets of data storage, each with date and time stamp, the units also enable the easy recalling of data for record keeping requirements. Designed and manufactured according to Lovibond® quality standards, the devices are equipped with replaceable electrodes to ensure long-life functionality in the field.

Applications:

- Boiler Water
- Cooling Water
- Drinking Water Treatment
- Pool Water Control
- Pool Water Treatment
- Waste Water Treatment

Products:

Title	Parameter and Range	Part Number
SD 50 pH	pH 0 - 14	194800-16
SD 50 in case	pH 0 - 14	194830-16
SD 60 ORP/Redox	Redox -1800 - 1800 mV	194801-16
SD 70 Con	Conductivity 0 - 20 ms/cm	194802-16
SD 80 TDS	TDS 0 - 10000 ppm	194803-16
SD 90 Salt	Salinity 0 - 2 %	194804-16